

Quad Custom Boot


SUBMITTAL



- Single unit boot provides for 4 pipe penetration
- 2 - 3/8 - 1" OD Boot and 2 - 1" - 2" OD Boot
- Used with standard **L-Arden** roof curbs
- Custom curb and boot configurations available
- Standard and optional features available may be viewed on curb literature page

PROJECT
LOCATION
ARCHITECT
ENGINEER
CONTRACTOR

ADVANCE OZONE RESISTANCE	EPDM 70HOUR @ 500 pphm
HIGH TEMPERATURE RESISTANCE Tested to Intermittent Continuous	+135°C (+275°F) +100°C (+212°F)
LOW TEMPERATURE RESISTANCE	-55°C (+67°F)



QTY	TOP A X B	C	MAT.	NOTE

BASE CURB	STRAIGHT • SRC	CANTED • CRC	RAISED-CANT • R-CRC

QTY	TYPE	O.D.	I.D.	HEIGHT 'H'	RAISE 'R'	GA.	MAT.	NOTE

Please be advised that the purpose of this submittal is to exhibit the overall dimensions of this product. Pictures and drawings do not give entire detail of product and are not portrayed to scale. L-Arden reserves the right to alter this submittal without notification.

72 Putnam Street • Paterson, NJ 07524 • 973-523-6400 • Fax 973-523-8282



WWW.L-ARDEN.COM

QPB.01.21-S